

DECORQUARZ

Quartz water-paint

FOR EXTERNAL USE

DECOR SYSTEM



Quartz based wall picture, for interior and exterior application, with acrylic resin. Have a very good covering and high UV and bad weather conditions resistance.

Type of support:

traditional or pre-mixed plasters, old painted plaster and prefabricated in concrete.

Preparation:

All substrates must be dry, thoroughly clean, in uniform absorption and appearance.

Non-bondable surface coatings must be completely removed. Apply an undercoat like "Deckfondo" (see technical data sheet).

Allways apply a hand of "Plioflex" Decora.

Precautions:

Unsuitable weather conditions may affect negatively the drying time, compromising the performance and aesthetic characteristics of the product. It is therefore recommended to apply in weather conditions given below. The filmation process takes place in about 15 days under optimum conditions (20°C R.U. 60%). Where there are violent rainings before the unprotected paint is completely dried, could highlight bad-looking stains by translucent appearance. This phenomenon, of a temporary nature, does not affect the quality of the product, but it can be mitigated, waiting for the next rainy events.

Packaging: Lt.15 Lt.4 Lt.0,75

Available colors:

WHITE and color chart,
COLLEZIONE 1000 and
COLLEZIONE 2000

Composition:

Dispersion of fine selected mineral fillers and titanium dioxide, with bactericidal additives suitable for sustainable conservation of the product.

Labelling:

In accordance with EC Regulation 1272/2008 (CLP), the preparation is labeled as follows: It does not require special labelling.

Type of waste:

empty bucket: special or similar to urban.

Bucket with waste: special.

Storage:

min T°: 5°C, max T°: 30°C.

Stability:

360 days in original containers

The above technical information are the result of accurate laboratory tests and experience practices. However, since the product is used often outside of our control, We can only guarantee its quality. These Information is subject to possible updates by the company

APPLICATION



BRUSH, ROLLER, SPRAY EQUIPMENT

www.coloridecora.it

COLORI DECORA Srl.
BASTIA UMBRA/PERUGIA
06083 Zona Ind.le - via degli Olmi, 10
Tel. 075 - 800 45 64 - Fax 075 - 800 48 76
e-mail: decora@coloridecora.it



SPECIFICATION:	
Environmental conditions:	T °min: 5 °C • T °max: 30 °C • U.R.max: 65%
Drying:	TACT: 2-3h RECOATABLE: 6 -8h
Dilution:	Water, 20-30% depending on the substrate
Appearance:	MATT
Specific gravity:	1,600 kg/L +/- 0,03
Solids content:	73% +/- 2
PH:	8-8,5
Cover rate:	<i>One hand:</i> 7-8 m ² /liter depending on the surface absorption