

# ARMONIA

## Transpiring water-based paint

### FOR INTERIOR

Transpiring water-based paint for interior, with good hiding power and cover rate.

#### Type of support:

Traditional or pre-mixed plasters, plasterboard or old painted plasters and precast in concrete.

#### Preparation:

All surfaces must be dry, clean thoroughly, in uniform absorption and appearance. On gypsum plaster is recommended to apply a hand of water-based insulator primer ISOLACRIL DECORA (see data sheet).

#### APPLICATION



BRUSH, ROLLER, SPRAY EQUIPMENT

#### TECHNICAL DATA:

<b>Environmental conditions:</b>	T °min: 5 °C • T °max: 30 °C • U.R.max: 65%
<b>Drying:</b>	DRY TO TOUCH: 2-3h RECOATABLE: 5-6h
<b>Dilution:</b>	Water 30-40% depending on the substrate
<b>Appearance:</b>	MATT
<b>Specific gravity:</b>	1,68 kg/L +/- 0,03
<b>Solids contentt:</b>	68% +/- 2
<b>pH:</b>	8-8,5
<b>Practical cover rate:</b>	<i>One hand:</i> 9-10 m <sup>2</sup> /L depending on the surface absorption



**Packaging:** Lt.15 Lt.4

#### Colors available:

White and color chart DECORA INTERNI

#### Composition:

Dispersion of selected mineral fillers and titanium dioxide, with bactericidal additives acts for the sustainable conservation of the product in vinyl resin dispersion.

#### Labelling:

In accordance with EC Regulation 1272/2008 (CLP), the preparation is labeled as follows: no special labeling is required.

#### Type of waste:

Empty bucket: special or similar to urban.

Bucket with waste: special.

#### Storage:

T °min: 5 °C, T °max: 30 °C.

#### Stability:

**360 days in the original containers**

The above technical information are the result of accurate laboratory tests and practical experience. However, since the product is often used outside our control, we can not guarantee that the quality. This information is subject to possible updates from the company

[www.coloridecora.it](http://www.coloridecora.it)

COLORI DECORA Srl.  
BASTIA UMBRA/PERUGIA  
06083 Zona Ind.le - via degli Olmi, 10  
Tel. 075 - 800 45 64 - Fax 075 - 800 48 76  
e-mail: decora@coloridecora.it

