ACRILUX ALL'ACQUA

Acrylic water repellent treatment Glossy effect INTERIOR / ESTERIOR



Water based trasparent paint with acrylic resins.

Specifically designed for hydrorepellent trattament on various surfaces, giving glossy apparence to the surfaces.

Type of support:

Concrete, bricks, stone.

Preparation:

All surfaces must be dry, clean thoroughly, in uniform absorption and appearance.

Precaution:

Do not apply on surfaces in horizontal or with presence of humidity.

APPLICATION

BRUSH, SPRAY EQUIPMENT



TECHNICAL DATA:	
Environmental conditions:	T°min: 5°C •T°max: 30° C •U.R.max: 65%
Drying:	DRY TO TOUCH: 2-4h RECOATABLE: 8-12 h
Dilution:	Water max 20%
Appearance:	TRASPARENT, GLOSSY EFFECT
Specific gravity:	1,000 kg/L +/- 0,02
Solids content:	36% +/- 0,5
Cover rate:	One hand: 10-12 m²/Litri depending on the surface absorption

Packaging: Lt.20 Lt.5 Lt.1

Composition:

Acrylic resins in dispersion.

Labelling:

In accordance with EC Regulation 1272/2008 (CLP), the preparation is labeled as follows: no labelling is required.

Type of waste:

Empty tank: special or similar to

urban

Tank with waste: special.

Storage:

T°min: 5°C, T°max: 30° C.

Stability:

360 days in original containers

The above technical information is the result of careful laboratory tests and practical experience. However, since that the product is often used outside of our control, we can not guarantee its quality. this information are subject to possible updates by the company



