

DECK FONDO MEDIO AI SILOSSANI

INTERIOR / ESTERIOR

Undercoat filler render, fine grained, for interior and exterior application, based on acryl and siloxane resins.

Type of support:

Civil traditional or premixed plaster, plasterboard and concrete.

Preparation:

All substrates must be dry, thoroughly clean, in uniform absorption and appearance.

In case of chalking (plaster) or non.bondable surfaces (old paintings), we recommend restoring the integrity of support through mechanical scraping or hydro washing.



Packaging: Lt.15 Lt.4

Available colors:

WHITE

Composition:

Selected mineral fillers, with maximum thickness of 600 micron, in acrylic and siloxane dispersion.

Labelling:

In accordance with the Rules CE1272/2008 (CLP), the preparation is labeled as follows: it does not require special labeling.

Type of waste:

Empty bucket: special or similar to urban.

Bucket with waste: special.

Storage:

T[°]min: 5°C, T[°]max: 30°C.

Stability:

360 days in original containers

The above technical information are the result of accurate laboratory tests and experience practices. However, since the product is used often outside of our control, We can only guarantee its quality. These Information is subject to possible updates by the company

APPLICATION



BRUSH, ROLLER

TECHNICAL DATA:

Environmental conditions:	T [°] min: 5°C • T [°] max: 30°C • U.R.max: 65%
Drying:	DRY TO TOUCH: 2-3h RECOATABLE: 5-6 h
Dilution:	Water 10-15% depending on the substrate absorption
Appearance:	Granular, Matt
Specific gravity:	1,660 Kg/L +/- 0,03
Solids content:	70% +/- 2
pH:	8-8,5
Cover rate:	<i>One hand:</i> 5-6 m ² /Lt
Particle size:	0,6 mm

www.coloridecora.it

COLORI DECORA Srl.
BASTIA UMBRA/PERUGIA
06083 Zona Ind.le - via degli Olmi, 10
Tel. 075 - 800 45 64 - Fax 075 - 800 48 76
e-mail: decora@coloridecora.it

