

DECK FONDO MEDIO ACRILICO

ESTERIOR/INTERIOR



Undercoat filler render, fine grained, for interior and exterior application

Type of support:

Civil traditional or premixed plaster, plasterboard and concrete.

Preparation:

All substrates must be dry, thoroughly clean, in uniform absorption and appearance.

In case of chalking (plaster) or non.bondable surfaces (old paintings), we recommend restoring the integrity of support through mechanical scraping or hydro washing.

Packaging: Lt.15 Lt.4

Available colors:

WHITE

Composition:

Selected mineral fillers, with maximum thickness of 600 micron, in acrylic resin dispersion .

Labelling:

In accordance with EC Regulation 1272/2008 (CLP), the preparation is labeled as follows: It does not require special labelling.

Type of waste:

empty bucket: special or similar to urban.

Bucket with waste: special.

Storage:

T[°]min: 5°C, T[°]max: 30 °C.

Stability:

360 days in original containers

The above technical information are the result of accurate laboratory tests and experience practices. However, since the product is used often outside of our control, We can only guarantee its quality. These Information is subject to possible updates by the company

APPLICATION



BRUSH, ROLLER

TECHINCAL DATA:

Environmental conditions:	T [°] min: 5°C • T [°] max: 30 °C • U.R.max: 65%
Drying:	DRY TO TOUCH: 2-3h RECOATABLE: 5-6 h
Dilution:	Water 10-15% depending on the substrate absorption
Appearance:	Granular, Matt
Specific gravity:	1,660 Kg/L +/- 0,03
Solids content:	72% +/- 2
pH:	8-8,5
Cover rate:	<i>One hand:</i> 5-6 m ² /Lt depending on the substrate absorption
Particle size:	Max 0,6 mm

www.coloridecora.it

COLORI DECORA Srl.
BASTIA UMBRA/PERUGIA
06083 Zona Ind.le - via degli Olmi, 10
Tel. 075 - 800 45 64 - Fax 075 - 800 48 76
e-mail: decora@coloridecora.it

