

IDEALSTUK

FILLER IN PASTE

IDEALSTUK is a water-borne filler in paste for interior use for levelling imperfections both on woodwork and wall.

The product can be used to fill cracks and depressions, making the surface even. IDEALSTUK is easy to sand, assures a good base for paints to adhere to and features good adhesion. Ready to use.

Preparation:

All surfaces must be dry, clean thoroughly. In the case of chalk (plaster), or flaking (Old paint) we suggest you to restore the integrity of the support through mechanical scraping or pressure washing.

Application:

Apply with metal trowel. If diluted with water use brush or spray equipment. In case of high thickness (over 2mm) do it in more successive applications.

Precaution:

Close the can after partial use.

APPLICATION



METAL TROWEL

TECHNICAL DATA:

Environmental conditions:	T°min: 5°C •T°max: 30°C •U.R.max: 65%
Drying:	DRY TO TOUCH: 2 h SANDING: 2-6 h depending on the applied thickness
Cover rate:	1-2 m ² /Kg per 500 µm of thickness
Appearance:	MATT
Dilution:	READY TO USE



Packaging: Lt.15 Lt.4

Colour:

WHITE

Composition:

Calcium carbonate and titanium dioxide in vinylic dispersion.

Labelling:

In accordance with EC Regulation 1272/2008 (CLP), the preparation is labeled as follows: no labelling is required.

Type of waste:

Empty tank: special or similar to urban.

Tank with waste: special.

Storage:

T°min: 5°C, T°max: 30°C.

Stability:

360 days in original containers

The above technical information is the result of careful laboratory tests and practical experience. However, since that the product is often used outside of our control, we can not guarantee its quality. This information are subject to possible updates by the company