

IDROREP HE 328

SILOSSANICO ALL'ACQUA

Siloxane water repellent treatment
INTERIOR / ESTERIOR



Packaging: Lt.20 Lt.5 Lt.1

Composition:

Acrylic and siloxane resins in dispersion.

Labelling:

In accordance with EC Regulation 1272/2008 (CLP), the preparation is labeled as follows: no labelling is required.

Type of waste:

Empty tank: special or similar to urban.
Tank with waste: special.

Storage:

T°min: 5°C, T°max: 30°C.

Stability:

360 days in original containers

The above technical information is the result of careful laboratory tests and practical experience. However, since that the product is often used outside of our control, we can not guarantee its quality. This information are subject to possible updates by the company

Water based transparent paint with fine acrylic resins modified with polysiloxane resins.

Specifically designed for hydrorepellent treatment on various surfaces, without modifying the final aspect.

Type of support:

Concrete, bricks, stone.

Preparation:

All surfaces must be dry, clean thoroughly, in uniform absorption and appearance.

Precaution:

Do not apply on surfaces in horizontal or with presence of humidity.

APPLICATION

BRUSH, SPRAY EQUIPMENT



TECHNICAL DATA:

Environmental conditions:	T°min: 5°C • T°max: 30° C • U.R.max: 65%
Drying:	DRY TO TOUCH: 4-6h RECOATABLE: 8-10 h
Dilution:	Water max 10%
Appearance:	TRASPARENT
Specific gravity:	1,020 kg/L +/- 0,02
Solids content:	10% +/- 0,5
Cover rate:	One hand: 6-10 m ² /Litri depending on the surface absorption

www.coloridecora.it

COLORI DECORA Srl.
BASTIA UMBRA/PERUGIA
06083 Zona Ind.le - via degli Olmi, 10
Tel. 075 - 800 45 64 - Fax 075 - 800 48 76
e-mail: decora@coloridecora.it

