

# ISOGUM ALL'ACQUA

Acrylic water repellent treatment  
Wet effect

INTERIOR / ESTERIOR

Water based transparent paint with acrylic resins.  
Specifically designed for hydrorepellent treatment on various surfaces,  
giving wet effect on the surfaces.

## Type of support:

Concrete, bricks, stone.

## Preparation:

All surfaces must be dry, clean thoroughly, in uniform absorption and appearance.

## Precaution:

Do not apply on surfaces in horizontal or with presence of humidity.

## APPLICATION



BRUSH, SPRAY EQUIPMENT

## TECHNICAL DATA:

Environmental conditions:	T °min: 5 °C • T °max: 30 °C • U.R.max: 65%
Drying:	DRY TO TOUCH: 2-4h RECOATABLE: 8-12 h
Dilution:	Water max 20%
Appearance:	TRASPARENT WET EFFECT
Specific gravity:	1,000 kg/L +/- 0,02
Solids content:	16% +/- 0,5
Cover rate:	One hand: 8-10 m <sup>2</sup> /Litri depending on the surface absorption



**Packaging:** Lt.20 Lt.5 Lt.1

## Composition:

Acrylic resins in dispersion.

## Labelling:

In accordance with EC Regulation 1272/2008 (CLP), the preparation is labeled as follows: no labelling is required.

## Type of waste:

Empty tank: special or similar to urban.

Tank with waste: special.

## Storage:

T °min: 5 °C, T °max: 30 °C.

## Stability:

**360 days in original containers**

The above technical information is the result of careful laboratory tests and practical experience. However, since that the product is often used outside of our control, we can not guarantee its quality. this information are subject to possible updates by the company

[www.coloridecora.it](http://www.coloridecora.it)

COLORI DECORA Srl.  
BASTIA UMBRA/PERUGIA  
06083 Zona Ind.le - via degli Olmi, 10  
Tel. 075 - 800 45 64 - Fax 075 - 800 48 76  
e-mail: decora@coloridecora.it

