

ISOLACRIL

WATER-BASED

Acrylic fixative-bonding for walls



ISOLACRIL is a fixative-insulating product, acrylic-based, offering high resistance to alkali and excellent strengthening power.

Type of support:

It suits as insulation on chalking surface to uniform the absorption. On old paint after brush and scrape to remove the flaking parts. It's recommended on gypsum plaster.

Preparation:

All surfaces must be dry, clean thoroughly, in uniform absorption and appearance.

Remove the old paints without good adhesion and flaking parts.

APPLICATION



BRUSH, SPRAY EQUIPMENT

SPECIFICATIONS:	
Environmental conditions:	T°min: 5°C • T°max: 30°C • U.R.max: 65%
Drying:	6-8 h
Dilution:	With Water 1:5
Appearance:	TRANSPARENT
Specific gravity:	1,00 kg/L +/- 0,02
Solids content:	44% +/- 2
PH:	8-8,5
Cover rate:	<i>One hand:</i> 10-12 m ² /Litri depending on the surface absorption

Packaging: Lt.20 Lt.5 Lt.1

Composition:

Acrylic resins in dispersion

Labelling:

In accordance with EC Regulation 1272/2008 (CLP), the preparation is labeled as follows: no labelling is required.

Precaution:

Dilute as indicated and apply with brush or spray equipment. Remember to adjust the dilution so that the support does not get shiny after drying.

Type of waste:

Empty tank: special or similar to urban.

Tank with waste: special.

Storage:

T°min: 5°C, T°max: 30°C.

Stability:

360 days in original containers

The above technical information is the result of careful laboratory tests and practical experience. However, since that the product is often used outside of our control, we can not guarantee its quality. This information are subject to possible updates by the company