

ISOSAN ALL'ACQUA

Fixative-insulating product, based on siloxane resins



ISOSAN is a fixative-insulating product, based on siloxane resins, offering high resistance to alkali and excellent strengthening power.

Type of support:

It suits as insulation on chalking surface to uniform the absorption. On old paint after brush and scrape to remove the flaking parts. It's recommended on gypsum plaster.

Preparation:

All surfaces must be dry, clean thoroughly, in uniform absorption and appearance.

Remove the old paints without good adhesion and flaking parts.

In case of new substrate, wait at least 4 weeks.

Packaging: Lt.20 Lt.5

Composition:

Acrylic resin, siloxane resin

Labeling:

In accordance with EC Regulation 1272/2008 (CLP), the preparation is labeled as follows: no labelling is required.

Type of waste:

Empty tank: special or similar to urban.

Tank with waste: special.

Storage:

T[°]min: 5 °C, T[°]max: 30 °C.

Stability:

360 days in original containers

The above technical information is the result of careful laboratory tests and practical experience. However, since that the product is often used outside of our control, we can not guarantee its quality. this information are subject to possible updates by the company

APPLICATION

BRUSH



TECHNICAL DATA:

Environmental conditions:	T [°] min: 5 °C • T [°] max: 30 °C • U.R.max: 65%
Drying:	4-6h
Dilution:	Water untill 100%
Appearance:	TRANSPARENT
Specific gravity:	1,030 kg/L +/- 0,03
Solids content:	6% +/- 1
pH:	10
Cover rate:	<i>One hand:</i> 8-10 m ² /Lt

www.coloridecora.it

COLORI DECORA Srl.
BASTIA UMBRA/PERUGIA
06083 Zona Ind.le - via degli Olmi, 10
Tel. 075 - 800 45 64 - Fax 075 - 800 48 76
e-mail: decora@coloridecora.it

