

# PLIOFLEX ALL'ACQUA

## WATER-BASED

Ultrafine fixative for walls



PLIOFLEX ALL'ACQUA is a clear water-based fixative-insulating agent, formulated with an acrylic dispersion of very fine particles.

It's resistant to alkali, it has a good strengthening power thanks to a strong wetting power and to the very small particle size that ensures a high penetrating capacity even on deteriorated but compact substrates. Good for interior and exterior use.

### Type of support:

Traditional or pre-mixed plasters, plasterboard or old painted plasters and precast in concrete.

### Preparation:

New walls: wait at least 4 week of seasoning. Wash the surface in reinforced concrete to remove trace of solvent.

Old walls: all surfaces must be dry, clean thoroughly, in uniform absorption and appearance.

Remove the old paints without good adhesion and flaking parts.

## APPLICATION



BRUSH, SPRAY EQUIPMENT

SPECIFICATIONS:	
Environmental conditions:	T °min: 5 °C • T °max: 30 °C • U.R.max: 65%
Drying:	8-12 hours
Dilution:	Water up to 100%
Appearance:	CLEAR
Specific gravity:	1,00 kg/L +/- 0,02
Solids content:	9% +/- 2
PH:	8-8,5
Cover rate:	<i>One hand: 8-10 m<sup>2</sup>/Litri depending on the surface absorption</i>

Packaging: Lt.20 Lt.5 Lt.1

### Composition:

Acrylic resins in dispersion of fine particles.

### Labelling:

In accordance with EC Regulation 1272/2008 (CLP), the preparation is labeled as follows: no labelling is required.

### Precaution:

Dilute as indicated and apply with brush or spray equipment. Remember to adjust the dilution so that the support does not get shiny after drying.

### Type of waste:

Empty tank: special or similar to urban.

Tank with waste: special.

### Storage:

T °min: 5 °C, T °max: 30 °C.

### Stability:

**360 days in original containers**

The above technical information is the result of careful laboratory tests and practical experience. However, since that the product is often used outside of our control, we can not guarantee its quality. this information are subject to possible updates by the company

[www.coloridecora.it](http://www.coloridecora.it)

COLORI DECORA Srl.  
BASTIA UMBRA/PERUGIA  
06083 Zona Ind.le - via degli Olmi, 10  
Tel. 075 - 800 45 64 - Fax 075 - 800 48 76  
e-mail: decora@coloridecora.it

